

V形端面油封



代号	名称	截面图	材料	压力	温度	圆周速度	特点							
VR	V形端面油封		橡胶	0	NBR -40至100 FKM -20至200	≤12	固定在旋转体上密封端面							
d	b	h	d	b	h	d	b	h	d	b	h	d	b	h
2.5	1.5	3	22	4	7.5	63	6	15.5	153	8	14.5	745	15	25
3.2	2	3.7	22	4	10.5	67	6	11	153	8	20.5	785	15	25
4	2	3.7	25	4	7.5	67	6	15.5	162	8	14.5	825	15	25
4	2	5.2	25	4	10.5	72	6	11	162	8	20.5	865	15	25
5	2	3.7	27	4	7.5	72	6	15.5	171	8	14.5	910	15	25
5	2	5.2	27	4	10.5	76	6	11	171	8	20.5	955	15	25
6	2	3.7	29	4	7.5	76	6	15.5	180	8	14.5	1000	15	25
6	2	5.2	29	4	10.5	81	6	11	180	8	20.5	1045	15	25
7	2	3.7	31	4	7.5	81	6	15.5	180	15	25	1090	15	25
7	2	5.2	31	4	10.5	85	6	11	198	15	25	1135	15	25
9	3	5.5	34	4	7.5	85	6	15.5	225	15	25	1180	15	25
9	3	7.7	34	4	10.5	90	6	11	247	15	25	1225	15	25
10.5	3	5.5	36	5	9	90	6	15.5	270	15	25	1270	15	25
10.5	3	7.7	36	5	13	99	7	12.8	292	15	25	1315	15	25
11.7	3	5.5	40	5	9	99	7	18	315	15	25	1360	15	25
12.5	3	5.5	40	5	13	108	7	12.8	337	15	25	1405	15	25
12.5	3	7.7	45	5	9	108	7	18	360	15	25	1450	15	25
14	3	5.5	45	5	13	117	7	12.8	405	15	25	1495	15	25
14	3	7.7	49	5	9	117	7	18	450	15	25	1540	15	25
16	3	5.5	49	5	13	126	7	12.8	495	15	25	1585	15	25
16	3	7.7	54	5	9	126	7	18	540	15	25	1630	15	25
18	4	7.5	54	5	13	135	7	12.8	600	15	25	1675	15	25
18	4	10.5	58	5	9	135	7	18	630	15	25	1720	15	25
20	4	7.5	58	5	13	144	8	14.5	670	15	25	1765	15	25
20	4	10.5	63	6	11	144	8	20.5	705	15	25	1810	15	25
其他截面														
VL 型														
VS 型														