



代号	名称	截面图	材料	压力	温度	圆周速度	特点
EP	E形四氟油封		橡胶+四氟	≤30	NBR-40至100 FKM -20至200	≤15	耐高压, 耐磨

D	d	L	O形圈规格	D	d	L	O形圈规格	d	D	L	O形圈规格	d	D	L	O形圈规格
8	3.1	2.2	2.90 x 1.78	135	119.5	6.3	116.84 x 5.33	6	10.9	2.2	7.65 x 1.78	120	131	4.2	123.42 x 3.53
10	5.1	2.2	4.80 x 1.8	140	124.5	6.3	123.19 x 5.33	8	12.9	2.2	9.5 x 1.8	125	136	4.2	129.77 x 3.53
12	7.1	2.2	6.70 x 1.8	150	134.5	6.3	132.72 x 5.33	10	14.9	2.2	11.8 x 1.8	130	141	4.2	136.12 x 3.53
14	9.1	2.2	8.75 x 1.8	160	144.5	6.3	142.24 x 5.33	12	16.9	2.2	14.00 x 1.78	135	146	4.2	139.29 x 3.53
15	10.1	2.2	9.25 x 1.78	170	154.5	6.3	151.77 x 5.33	14	18.9	2.2	15.60 x 1.78	140	151	4.2	145.64 x 3.53
16	11.1	2.2	10.82 x 1.78	180	164.5	6.3	164.47 x 5.33	15	19.9	2.2	17.17 x 1.78	150	161	4.2	151.99 x 3.53
18	13.1	2.2	12.42 x 1.78	190	174.5	6.3	170.82 x 5.33	16	20.9	2.2	17.17 x 1.78	160	171	4.2	164.69 x 3.53
20	15.1	2.2	14.00 x 1.78	200	184.5	6.3	183.52 x 5.33	18	22.9	2.2	18.77 x 1.78	170	181	4.2	177.39 x 3.53
22	17.1	2.2	17.17 x 1.78	210	194.5	6.3	189.87 x 5.33	20	27.5	3.2	21.89 x 2.62	180	191	4.2	183.74 x 3.53
25	20.1	2.2	18.77 x 1.78	220	204.5	6.3	202.57 x 5.33	22	29.5	3.2	25.07 x 2.62	190	201	4.2	196.44 x 3.53
28	23.1	2.2	21.95 x 1.78	230	214.5	6.3	208.92 x 5.33	25	32.5	3.2	28.24 x 2.62	200	215.5	6.3	208.92 x 5.33
30	25.1	2.2	25.12 x 1.78	240	224.5	6.3	221.62 x 5.33	28	35.5	3.2	31.42 x 2.62	210	225.5	6.3	215.27 x 5.33
32	27.1	2.2	26.70 x 1.78	250	234.5	6.3	234.32 x 5.33	30	37.5	3.2	32.99 x 2.62	220	235.5	6.3	227.97 x 5.33
35	30.1	2.2	29.87 x 1.78	280	264.5	6.3	266.07 x 5.33	32	39.5	3.2	34.59 x 2.62	240	255.5	6.3	247.02 x 5.33
40	32.5	3.2	31.42 x 2.62	300	284.5	6.3	278.77 x 5.33	35	42.5	3.2	37.77 x 2.62	250	265.5	6.3	253.37 x 5.33
42	34.5	3.2	32.99 x 2.62	320	304.5	6.3	304.17 x 5.33	36	43.5	3.2	39.34 x 2.62	280	301	8.1	291.47 x 7.00
45	37.5	3.2	36.17 x 2.62	350	329	8.1	329.57 x 7.00	40	51	4.2	44.04 x 3.53	300	321	8.1	304.17 x 7.00
48	40.5	3.2	39.34 x 2.62	400	379	8.1	267.67 x 7.00	42	53	4.2	47.22 x 3.53	320	341	8.1	329.57 x 7.00
50	42.5	3.2	40.94 x 2.62	420	399	8.1	393.07 x 7.00	45	56	4.2	50.39 x 3.53	350	371	8.1	354.97 x 7.00
52	44.5	3.2	44.12 x 2.62	450	429	8.1	417.96 x 7.00	48	59	4.2	53.57 x 3.53	360	381	8.1	367.67 x 7.00
55	47.5	3.2	45.69 x 2.62	480	459	8.1	456.06 x 7.00	50	61	4.2	53.57 x 3.53	400	421	8.1	405.26 x 7.00
60	52.5	3.2	52.07 x 2.62	500	479	8.1	468.76 x 7.00	52	63	4.2	56.74 x 3.53	420	441	8.1	430.66 x 7.00
63	55.5	3.2	53.64 x 2.62	600	579	8.1	582.68 x 7.00	55	66	4.2	59.92 x 3.53	450	471	8.1	456.06 x 7.00
65	57.5	3.2	56.82 x 2.62	700	672	9.5	670.00 x 8.40	56	67	4.2	59.92 x 3.53	480	501	8.1	494.16 x 7.00
70	62.5	3.2	61.60 x 2.62	以上规格为孔用				60	71	4.2	63.09 x 3.53	500	521	8.1	506.86 x 7.00
75	67.5	3.2	66.34 x 2.62					63	74	4.2	66.27 x 3.53	600	621	8.1	608.08 x 7.00
80	69	4.2	66.27 x 3.53					65	76	4.2	69.44 x 3.53	700	728	9.5	713.00 x 8.40
85	74	4.2	72.62 x 3.53					70	81	4.2	75.79 x 3.53	以上规格为轴用			
90	79	4.2	78.97 x 3.53					75	86	4.2	78.97 x 3.53				
95	84	4.2	82.14 x 3.53					80	91	4.2	85.32 x 3.53				
100	89	4.2	88.49 x 3.53					85	96	4.2	88.49 x 3.53				
105	94	4.2	91.67 x 3.53					90	101	4.2	94.84 x 3.53				
110	99	4.2	98.02 x 3.53					95	106	4.2	101.19 x 3.53				
115	104	4.2	101.19 x 3.53					100	111	4.2	104.37 x 3.53				
120	109	4.2	107.54 x 3.53					105	116	4.2	110.72 x 3.53				
125	114	4.2	113.89 x 3.53					110	121	4.2	113.89 x 3.53				
130	119	4.2	117.07 x 3.53					115	126	4.2	120.24 x 3.53				